



JCT1055Z 55A SCR

Rev.A.1.1

DESCRIPTION:

With high ability to withstand the shock loading of large current, JCT1055Z SCR provides high dV/dt rate with strong resistance to electromagnetic interference. It is especially recommended for use on solid state relay, motorcycle, power charger, T-tools etc. From all three terminals to external heatsink, JCT1055Z provides a rated insulation voltage of 2500 V_{RMS} , complying with UL standards (File ref: E252906). Package TO-3P is RoHS compliant.

MAIN FEATURES

ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Value	Unit
Storage junction temperature range	T_{stg}	-40-150	
Operating junction temperature range	T_j	-40-125	
Repetitive peak off-state voltage ($T_j=25^\circ C$)	V_{DRM}	1000	V
Repetitive peak reverse voltage ($T_j=25^\circ C$)	V_{RRM}	1000	V
Average on-state current ($T_c=60^\circ C$)	$I_{T(AV)}$	35	A
RMS on-state current ($T_c=60^\circ C$)	$I_{T(RMS)}$	55	A
Non repetitive surge peak on-state current ($t_p=10ms, T_j=25^\circ C$)	I_{TSM}	700	mA
Non repetitive surge peak on-state current ($t_p=8.3ms, T_j=25^\circ C$)			

	GM	10	A
	(AV)	1	W

Peak gate power

P_{GM}



20

W

PTI -0.4

ORDERING INFORMATION

J CT 10 55 Z

FIG.1: Maximum power dissipation versus RMS on-state current**FIG.2:** RMS on-state current versus case temperature

JCT1055Z

JCT1055Z

ORDERING INFO

Order code	IGT(mA)	PackC	0.775.6.48 539.0 10.56 70.463.4 r11.48 563.32 7
------------	---------	-------	---

