



JX020Q 2A Sensitive SCR

Rev.A.1.0

DESCRIPTION:

The JX020Q SCR provides high dV/dt rate with strong resistance to electromagnetic interface. It is especially recommended for use on residual current circuit breaker, straight hair, igniter etc. Package TO-126 is RoHS compliant.

MAIN FEATURES

Symbol	Value	Unit
$I_{T(RMS)}$	2	A
V_{DRM}/V_{RRM}	600	V
I_{GT}	0.200	μA

ABSOLUTE MAXIMUM RATINGS


Parameter	Symbol	Value	Unit
Storage junction temperature range			
Operating junction temperature range	T_j	-40-125 ⁷	
Repetitive peak off-state voltage ($T_j=25^\circ C$)	V_{DRM}	600	V



Peak gate power	P_{GM}	2	W
Peak pulse voltage ($T_j=25^\circ\text{C}$; non-repetitive, off-state; FIG.7)	V_{pp}	0.5	kV

NOTE 1: Operating junction temperature T_j is up to 125°C when a resistor $10k\Omega$ is connected between Gate and Cathode. Without this resistor, the T_j is up to 110°C

ORDERING INFORMATION



MARKING




FIG.1: Maximum power dissipation versus
RMS on-state current




FIG.2: RMS on-state current versus case
temperature

FIG.7 ÖTest circuit for inductive and resistive loads to IEC-61000-4-5 standards. F



ORDERING INFORMATION

Order code	Voltage $V_{\text{DSM}}/V_{\text{RRM}}$ (V)	IGT)	Package	Base qty. (pcs)	Delivery mode
JX020Q	600		TO-126	500	Bulk Pack

Document Revision History

Date	Revision	Changes
Apr.12, 2023	A.1.0	Last update

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co.,Ltd assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information.