




ACJT1210-10E 12A TRIAC

Rev.A.1.0

DESCRIPTION:

The ACJT1210-10E triac is suitable for general purpose AC switching. It can be used as an ON/OFF function in applications such as heating regulation, induction motor starting circuits, for phase control operation in light dimmers, motor speed controllers. The ACJT1210-10E



energy such as those described in the IEC 61000-4-5 standards. Package(T)Tj -0.021 Tc 0.021 Tw 4.15 0 Td (TO)Tj 0 Tc 0 Tw 1.37 0 Td [(-)3 (2)]TJ 0.004

MAIN FEATURES

ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Value	Unit
Stage(j)6 (unc)14 (t)2 (i)6 (on )10 (t)2 (e)10 (m)-3T(p)10 (er)7 (at)140 (15)7 ne range	j	-40-125	
Repetitive peak off-state voltage((j)7 (T)]TJ 0 Tc 0 Tw 8.04 0 0 8.04 248.04 306.84 Tm (j)Tj -0.004			

		120	A
	I	132	
I t(-)10 (v)14 (al)6 (ue f)-8 (or)7=25 using(-)10 ((j)7 (t)]TJ 0 Tc 0 Tw 8.04 0 0 8.04 168.6s173.76 Tm (			

Peak pulse voltage ( $T_j=25$ ; non-repetitive, off-state; FIG.8)	$V_{pp}$	4.5	kV
--	----------	-----	----


**ELECTRICAL CHARACTERISTICS** ( $T_j=25$  unless otherwise specified)

Symbol	Test Condition	Quadrant	Value		Unit
$I_{GT}$	$V_D=12V$ $R_L=33$	- -	MAX.	10	mA
$V_{GT}$		- -	MAX.	1	V
$V_{GD}$	$V_D=V_{DRM}$ $T_j=125$ $R_L=3.3K$	- -	MIN.	0.2	V
$I_L$	$I_G=1.2I_{GT}$	-	MAX.	25	mA
				30	
$I_H$	$I_T=500mA$		MAX.	20	mA
$dV/dt$	$V_D=670V$ Gate Open $T_j=125$		MIN.	300	V/ $\mu s$
$(dI/dt)_c$	$(dV/dt)_c=10V/\mu s$ , $T_j=125$		MIN.	3	A/ms
$t_{on}$	$I_G=20mA$ $I_A=200mA$ $I_R=20mA$ $T_j=25$		TYP.	4	$\mu s$
$t_{off}$				50	
$V_{CL}$	$I_{CL}=0.1mA$ $t_p=1ms$		MIN.	1050	V


**STATIC CHARACTERISTICS**

Symbol	Parameter		Value(MAX.)	Unit
$V_{TM}$	$I_{TM}=17A$ $t_p=380\mu s$	$T_j=25$	1.45	V
$V_{TO}$	Threshold voltage	$T_j$		

ORDERING INFORMATION




**FIG.1** Maximum power dissipation versus RMS on-state current



**FIG.2:** RMS on-state current versus case temperature



FIG.8 Test circuit for inductive and resistive loads to IEC-61000-4-5 standards




**ORDERING INFORMATION**

<b>Order code</b>	<b>Voltage <math>V_{DRM}/V_{RRM}</math> (V)</b>	<b>IGT(mA)</b>	<b>Package</b>	<b>Base qty. (pcs)</b>	<b>Delivery mode</b>
<b>ACJT1210-10E</b>	<b>1000</b>	<b>10</b>	<b>TO-263</b>	<b>50</b>	<b>Tube</b>
<b>ACJT1210-10E-TR</b>				<b>800</b>	<b>Tape &amp; Reel</b>


**A**

PACKAGE MECHANICAL DATA



Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	9.90		10.20	0.390		0.402
B	14.70		15.80	0.579		0.622
C	9.40		9.60	0.37		0.378
D	2.40		2.70	0.094		0.106
E	1.20		1.50	0.047		0.059
F	0.75		0.85	0.029		0.033
G	1.00		1.50	0.039		0.059
H	4.40		4.70	0.173		0.185
J	2.30		2.70	0.091		0.106
K	0.38		0.55	0.015		0.022
L	0	0.10	0.25	0	0.004	0.010
M	1.25		1.35	0.049		0.053
P	1.20		1.50	0.047		0.059

FOOTPRINT-TO-263 (dimensions in mm)





Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document