



JST08E-800BW 8A TRIAC

Rev.A.1.2

## DESCRIPTION:

The JST08E-800BW triac is suitable for general purpose AC switching. It can be used as an ON/OFF function in

|                                                                                    |          |     |    |
|------------------------------------------------------------------------------------|----------|-----|----|
| Peak pulse voltage<br>( $T_j=25^\circ\text{C}$ ; non-repetitive, off-state; FIG.8) | $V_{pp}$ | 2.5 | kV |
|------------------------------------------------------------------------------------|----------|-----|----|

# ELECTRICAL CHARACTERISTICS (unless otherwise specified)

| Symbol   | Test Condition                                            | Quadrant | Value |     | Unit |
|----------|-----------------------------------------------------------|----------|-------|-----|------|
| $I_{GT}$ | $V_D=12V$ $R_L=33\Omega$                                  | - -      | MAX.  | 50  | mA   |
| $V_{GT}$ |                                                           | - -      | MAX.  | 1   | V    |
| $V_{GD}$ | $V_D=V_{DRM}$ $T_j=125^\circ\text{C}$<br>$R_L=3.3k\Omega$ | - -      | MIN.  | 0.2 | V    |

$I_L$   $I_G=1.2I_{GT}$

## ORDERING INFORMATION

| J                                 | ST     | 08              | E        | -800                         | BW              | -/                            |
|-----------------------------------|--------|-----------------|----------|------------------------------|-----------------|-------------------------------|
| JieJie Microelectronics Co., Ltd. | Triacs | $I_{T(RMS)}:8A$ | E:TO-263 | 800: $V_{DRM}/V_{RRM} 1800V$ | BW:IGT1-3 050mA | Blank:Tube<br>-TR:Tape & Reel |

## MARKING




FIG.1: Maximum power dissipation versus RMS on-state current



FIG.2: RMS on-state current versus case temperature

FIG.7: Relative variations of gate trigger current, holding current and latching current versus junction temperature






## ORDERING INFORMATION

| Order code      | Voltage<br>$V_{\text{DRM}}/V_{\text{RRM}}$ (V) | IGT(mA) | Package | Base qty.<br>(pcs) | Delivery mode |
|-----------------|------------------------------------------------|---------|---------|--------------------|---------------|
|                 |                                                | - -     |         |                    |               |
| JST08E-800BW    | 800                                            | 50      | TO-263  | 50                 | Tube          |
| JST08E-800BW-TR |                                                |         |         | 800                | Tape & Reel   |

## Document Revision History

| Date         | Revision | Changes                        |
|--------------|----------|--------------------------------|
| Apr.11, 2023 | A.1.0    | Last updated                   |
| Aug.11, 2025 | A.1.1    | Revise dV/dt & (dI/dt)c        |
| Oct.17, 2025 | A.1.2    | Revise PACKAGE MECHANICAL DATA |

PACKAGE MECHANICAL DATA



| Ref. | Dimensions  |      |       |        |      |       |
|------|-------------|------|-------|--------|------|-------|
|      | Millimeters |      |       | Inches |      |       |
|      | Min.        | Typ. | Max.  | Min.   | Typ. | Max.  |
| A    | 9.90        |      | 10.20 | 0.390  |      | 0.402 |
|      |             |      |       |        |      |       |
| B    | 14.70       |      | 15.80 | 0.579  |      | 0.622 |
|      |             |      |       |        |      |       |
| C    | 9.40        |      | 9.60  | 0.370  |      | 0.378 |
|      |             |      |       |        |      |       |
| D    | 2.40        |      |       | 0.094  |      |       |
| E    | 1.20        |      | 1.50  | 0.047  |      | 0.059 |
| F    | 0.75        |      | 0.85  | 0.029  |      | 0.033 |
|      |             |      |       |        |      |       |
|      |             |      |       |        |      |       |
|      |             |      |       |        |      |       |
|      |             |      |       |        |      |       |



DELIVERY MODE



Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.



is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.

Copyright © 2025 Jiangsu JieJie Microelectronics Co., Ltd. All rights reserved.